

GLOSSARY OF ABBREVIATIONS AND ACRONYMS

A

A	amplitude; augmentation; away (altitude intercept); Arctic/Antarctic (air mass).
a	semimajor axis.
<i>a</i>	altitude intercept ($H_o \sim H_c$); altitude factor (change of altitude in 1 minute of time from meridian transit); assumed.
ABAND	abandoned.
AC	alternating current; altocumulus.
ACC	Antarctic Circumpolar Current.
add'l	additional.
ADF	automatic direction finder.
ADIZ	air defense identification zone.
AEB	acquisition exclusion boundary.
AERO	aeronautical.
AF	audio frequency.
AFC	automatic frequency control.
AGC	automatic gain control.
AISM	Association Internationale de Signalisation Maritime (International Association of Lighthouse Authorities).
aL	assumed latitude.
Al., Alt,	alternating (light).
A.L.R.S.	<i>Admiralty List of Radio Signals</i> .
am	amber.
AM	amplitude modulation.
AM	ante meridian (before noon).
AMVER	Automated Mutual-assistance Vessel Rescue system.
Anch	anchorage.
ANMS	Automated Notice to Mariners System.
antilog	antilogarithm.
AP	assumed position.
approx.	approximate, approximately.
ARPA	automatic radar plotting aid.
ASAM	anti-ship action message.
ASF	Additional Secondary Phase Factor.
AT	atomic time.
AU	astronomical unit.
AUSREP	Australian Ships Reporting System.
al	assumed longitude.

B

B	atmospheric pressure correction (altitude); bearing, bearing angle.
Bdy Mon	boundary monument.

BFO	beat frequency oscillator.
BIH	Bureau Internationale de l'Heure.
BIPM	International Bureau of Weights and Measures.
bk	broken.
bkw	breakwater.
bl	blue.
BM	bench mark.
Bn	beacon.
Bpgc	bearing per gyrocompass.
br	breakers.
Brg.	bearing (as distinguished from bearing angle).
bu	blue.

C

C	Celsius (centigrade); chronometer time; compass (direction); correction; course, course angle; can; cylindrical; cove.
CALM	catenary anchor leg mooring.
CB	compass bearing.
CBDR	constant bearing, decreasing range.
CC	compass course; chronometer correction.
CCIR	International Radio Consultative Committee.
CCU	Consultative Committee for Units of the International Committee of Weights and Measures (CIPM).
CCZ	Coastal Confluence Zone.
cd	candela, candelas.
CD	chart datum.
CD-ROM	compact disk-read only memory.
CG	Coast Guard.
CE	chronometer error- compass error.
CFR	Code of Federal Regulations.
cec	centicycle.
cel	centilane.
CEP	circular probable error.
CES	coast earth station.
CFR	Code of Federal Regulations.
CGPM	General Conference of Weights and Measures.
CH	compass heading.
CIPM	International Committee of Weights and Measures.
Cl	clearance.

cm	centimeter(s).	DMAHTC	Defense Mapping Agency Hydrographic/Topographic Center.
CMG	course made good.	DNC	digital navigation chart.
Cn	course (as distinguished from course angle).	dol	dolphin.
co	coral.	DR	dead reckoning; dead reckoning position.
co-	the complement of (90° minus).	DRE	dead reckoning equipment.
COA	course of advance.	DRM	direction of relative movement.
COE	Committee on ECDIS (IHO).	DRT	dead reckoning tracer.
COG	course over ground.	Ds	dip short of horizon.
coL	colatitude.	DSC	digital selective calling.
colog	cologarithm.	DSD	double second difference.
corr.	correction.	DSVL	doppler sonar velocity log.
cos	cosine.	dur.	duration.
cot	cotangent.	DW	Deep Water Route.
cov	coversine.	DZ	danger zone.
CPA	closest point of approach.		
CPE	circular probable error.		
Cpgc	course per gyrocompass.		
cps	cycles per second.	E	east.
Cpsc	course per standard compass.	e	base of Napierian logarithms; origin of own ship's true vector.
Cp stg c	course per steering compass.		
CPU	central processing unit.		eccentricity.
crs	course.		electronic bearing line.
CRT	cathode-ray tube.	EBL	envelope to cycle difference; envelope to cycle discrepancy.
csc	cosecant.	ECD	electronic chart.
cup	cupola.	EC	electronic chart data base.
Cus Ho	customs house.	ECDB	electronic chart display and information system.
CW	continuous wave.	ECDIS	existence doubtful.
CZn	compass azimuth.		estimated date of departure.

D

D	deviation; dip (of horizon); distance; destroyed.	EEZ	exclusive economic zone.
d	declination (astronomical); altitude difference.	EGC	enhanced group calling.
d	declination change in 1 hour.	EHF	extremely high frequency.
dA	difference of longitude (time units).	E. Int.	equal interval; isophase.
DC	direct current.	EM	electromagnetic (underwater log).
deg.	degree(s).	em	other ship's true vector.
Dec.	declination.	ENC	electronic navigation chart.
Dec. Inc.	declination increment.	ENCDB	electronic navigation chart data base.
Dep.	departure.	EP	estimated position.
destr	destroyed.	EPIRB	Emergency Position Indicating Radio-beacon.
Dev.	deviation.	EPROM	erasable programmable read only memory.
DG	degaussing.	Eq.T	equation of time.
DGPS	differential global positioning system.	er	own ship's true vector.
DHQ	mean diurnal high water inequality.	ET	Ephemeris Time.
Dia	diaphone.	ETA	estimated time of arrival.
diff.	difference.	ETD	estimated time of departure.
Dist.	distance.	Exting	extinguished.
D. Lat.	difference of latitude.		
DLo	difference of longitude (arc units).	F	Fahrenheit; fast; longitude factor; phase correction (altitude); fixed (light)
DLQ	mean diurnal low water inequality.	f	latitude factor.
dm	decimeters.		

E

	east.
	base of Napierian logarithms; origin of own ship's true vector.
	eccentricity.
	electronic bearing line.
	envelope to cycle difference; envelope to cycle discrepancy.
	electronic chart.
	electronic chart data base.
	electronic chart display and information system.
	existence doubtful.
	estimated date of departure.
	exclusive economic zone.
	enhanced group calling.
	extremely high frequency.
	equal interval; isophase.
	electromagnetic (underwater log).
	other ship's true vector.
	electronic navigation chart.
	electronic navigation chart data base.
	estimated position.
	Emergency Position Indicating Radio-beacon.
	erasable programmable read only memory.
	equation of time.
	own ship's true vector.
	Ephemeris Time.
	estimated time of arrival.
	estimated time of departure.
	extinguished.

F

	Fahrenheit; fast; longitude factor; phase correction (altitude); fixed (light)
	latitude factor.

f	flattening or ellipticity.	Ho	observed altitude.
F.Fl.	fixed and flashing.	Hor	horizontal.
Fl.	flashing (light).	Hor Cl	horizontal clearance.
Fl. (2)	group flashing (light).	HP	horizontal parallax.
Fl. (2+1)	composite group flashing (light).	Hp	precomputed altitude.
fm(s)	fathom(s).	Hpgc	heading per gyrocompass.
FM	frequency modulation.	Hpsc	heading per standard compass.
Fog Det.	fog detector.	Hp stg c	heading per steering compass.
Fog Sig.	fog signal.	hr	rectified (apparent) altitude.
ft.	foot, feet.	hr.	hour, hrs., hours.
FTC	fast time constant.	hs	sextant altitude.

G

G	Greenwich; Greenwich meridian (upper branch); grid (direction); gravel; green.	H.W.F.&C.	high water full and change.
g	acceleration due to gravity; Greenwich meridian (lower branch).	HWI	high water interval, mean high water lunital interval.
GAT	Greenwich apparent time.	HWQ	tropic high water inequality.
GB	grid bearing.	Hz	Hertz.
GC	grid course.		
GCLWD	Gulf Coast Low Water Datum.		
GDOP	geometric dilution of precision.	I	instrument correction.
GE	gyro error.	i	inclination (of satellite orbit).
GH	grid heading.	IALA	International Association of Lighthouse Authorities.
GHA	Greenwich hour angle.	IAU	International Astronomical Union.
GMDSS	Global Maritime Distress and Safety System.	IC	index correction.
GMT	Greenwich mean time.	ICW	Intracoastal Waterway.
Gp. Fl.	group flashing.	IGLD	International Great Lakes Datum.
GP	geographical position.	IHB	International Hydrographic Bureau.
GPS	Global Positioning System.	IHO	International Hydrographic Organization.
Gr.	Greenwich.	IMO	International Maritime Organization.
GRI	group repetition interval.	in.	inch, inches.
GST	Greenwich sidereal time.	INM	International Nautical Mile.
GV	grid variation.	INMARSAT	International Maritime Satellite Organization.
GZn	grid azimuth.	INS	inertial navigation system.

H

h	altitude (astronomical); height above sea level; hours.	Int. Qk.	Interrupted quick flashing.
ha	apparent altitude.	ION	Institute of Navigation.
Hc	computed altitude.	I.Q.	interrupted quick flashing.
Hdg.	heading.	IR	interference rejection.
HE	heeling error; height of eye.	IRP	image-retaining panel.
HF	high frequency.	ISLW	Indian spring low water.
hf	height above sea level in feet.	ISO	International Order of Standardization; isophase (light).
HHW	higher high water.	ITU	International Telecommunications Union.
HHWI	higher high water interval.	IUGG	International Union of Geodesy and Geophysics.
Hk	hulk.	I.U.Q.	interrupted ultra quick flashing.
HLW	higher low water.	I.V.Q.	interrupted very quick flashing.
HLWI	higher low water interval.	IWW	Intracoastal Waterway.
hm	height above sea level in meters.		

I

instrument correction.
inclination (of satellite orbit).
International Association of Lighthouse Authorities.
International Astronomical Union.
index correction.

Intracoastal Waterway.
International Great Lakes Datum.
International Hydrographic Bureau.
International Hydrographic Organization.
International Maritime Organization.

J – K – L

J	irradiation correction (altitude).	mb	millibar(s).
K	Kelvin (temperature).	MC	magnetic course.
kHz	kilohertz.	mc	megacycle, megacycles; megacycles per second.
km	kilometer, kilometers.	MC&G	mapping, charting and geodesy.
kn	knot, knots.	MCPA	minutes to closest point of approach.
L	latitude; lower limb correction for moon.	Mer. Pass.	meridian passage.
l	difference of latitude; logarithm, logarithmic.	MF	medium frequency.
LAN	local apparent noon.	MGRS	military grid reference system.
LANBY	large automatic navigational buoy.	MH	magnetic heading.
LASH	lighter aboard ship.	MHHW	mean higher high water.
LAT	local apparent time.	MHHWL	mean higher high water line.
lat.	latitude.	MHW	mean high water.
LF	low frequency.	MHWI	mean high water lunitidal interval.
L.Fl.	long flashing.	MHWL	mean high water line.
LHA	local hour angle.	MHWN	neap high water or high water neaps.
LHW	lower high water.	MHWS	mean high water springs.
LHWI	lower high water interval.	MHz	megahertz.
LL	lower limb.	mi.	mile, miles.
LLW	lower low water.	mid	middle.
LLWD	lower low water datum.	min.	minute(s).
LLWI	lower low water interval.	MLLW	mean lower low water.
Lm	middle latitude; mean latitude.	MLLWL	mean lower low water line.
LMT	local mean time.	MLW	mean low water.
LNB	large navigational buoy.	MLWI	mean low water lunitidal interval.
LNG	liquefied natural gas.	MLWL	mean low water line.
LPG	liquefied petroleum gas.	MLWN	neap low water or low water neaps.
Log	logarithm, logarithmic.	MLWS	mean low water springs.
Loge	natural logarithm (to the base e).	mm	millimeters.
Log10	common logarithm (to the base 10).	Mn	mean range of tide.
Long.	longitude.	mo(s)	month(s).
LOP	line of position.	MODU	mobile offshore drilling unit.
LST	local sidereal time.	Mon	monument.
Lt.	light.	Mo.(U)	Morse Uniform (light).
Lt Ho	light house.	mph	miles per hour.
Lt V	light vessel.	MPP	most probable position.
LW	low water.	MRI	mean rise interval.
LWD	low water datum.	MRM	miles of relative movement.
LWI	low water interval; mean low water lunitidal interval.	ms	millisecond(s).
LWQ	tropic low water inequality.	MSC	Military Sealift Command.

M

M	celestial body; meridian (upper branch); magnetic (direction); meridional parts; nautical mile, miles; other ship.
m	meridian (lower branch); meridional difference; meter,(s); U.S. survey mile, miles; end of other ship's true vector; minutes.
mag.	magnetic; magnitude.
MARAD	United States Maritime Administration.
MB	magnetic bearing.

mb	millibar(s).
MC	magnetic course.
mc	megacycle, megacycles; megacycles per second.
MC&G	mapping, charting and geodesy.
MCPA	minutes to closest point of approach.
Mer. Pass.	meridian passage.
MF	medium frequency.
MGRS	military grid reference system.
MH	magnetic heading.
MHHW	mean higher high water.
MHHWL	mean higher high water line.
MHW	mean high water.
MHWI	mean high water lunitidal interval.
MHWL	mean high water line.
MHWN	neap high water or high water neaps.
MHWS	mean high water springs.
MHz	megahertz.
mi.	mile, miles.
mid	middle.
min.	minute(s).
MLLW	mean lower low water.
MLLWL	mean lower low water line.
MLW	mean low water.
MLWI	mean low water lunitidal interval.
MLWL	mean low water line.
MLWN	neap low water or low water neaps.
MLWS	mean low water springs.
mm	millimeters.
Mn	mean range of tide.
mo(s)	month(s).
MODU	mobile offshore drilling unit.
Mon	monument.
Mo.(U)	Morse Uniform (light).
mph	miles per hour.
MPP	most probable position.
MRI	mean rise interval.
MRM	miles of relative movement.
ms	millisecond(s).
MSC	Military Sealift Command.
MSI	maritime safety information.
MSL	mean sea level.
MTI	moving target indication.
MTL	mean tide level.
MWL	mean water level.
MWLL	mean water level line.
MZn	magnetic azimuth.

N

N	north; nun.
n	natural (trigonometric function).
Na	nadir.
NAD	North American Datum.
NASA	National Aeronautics and Space Administration.

NAUTO	nautophone.	PPI	plan position indicator.
NAVINFONET	Navigation Information Network.	PRF	pulse repetition frequency.
NAVSAT	Navy Navigation Satellite System.	Priv	private; privately.
NAVSSI	navigation sensor system interface.	PROHIB	prohibited.
NBDP	narrow band direct printing.	PRR	pulse repetition rate.
NBS	National Bureau of Standards.	Ps	south pole; south celestial pole.
NCS	network coordination station.	psc	per standard compass.
NESS	National Earth Satellite Service.	p stg c	per steering compass.
NGVD	National Geodetic Vertical Datum.	Pub.	publication.
NLT	not less than (used with danger bearing).	PV	prime vertical.
n. mi.	nautical mile(s).	Pyl	pylon.
NM	nautical mile, miles; notice to mariners.		
NMEA	National Marine Electronics Association.		
NMT	not more than (used with danger bearing).	Q	quick flashing.
NNSS	Navy Navigation Satellite System.	Q(3)	group quick flashing (3 flashes).
NOAA	National Oceanic and Atmospheric Administration.	Q(6)+L.Fl.	group quick flashing (6 flashes) plus a long flash.
NOS	National Ocean Service.	Q	Polaris correction.
NRML	new relative movement line.	QQ'	celestial equator.
NtM	notice to mariners.		
NWS	National Weather Service.		

O

Obsc	obscured.
Obs Spot	Observation spot.
Obstr	obstruction.
Oc.	occulting.
Oc.(2)	group occulting.
Oc.(2+1)	composite group occulting.
Occas	occasional.
ODAS	oceanographic data acquisition systems.
Or	orange.
OTC	officer in tactical command.
OTSR	Optimum Track Ship Routing.

P

P	atmospheric pressure; parallax; planet; pole; pillar.
p	departure; polar distance.
PA	position approximate.
PC	personal correction; personal computer.
PD	position doubtful.
PCA	polar cap absorption.
PCD	polar cap disturbance.
PCP	potential point of collision.
pgc	per gyrocompass.
P in A	parallax in altitude.
PM	pulse modulation.
PM	post meridian (after noon).
Pn	north pole; north celestial pole.
PPC	predicted propagation correction.
PPDB	point positioning data base.

PPI	plan position indicator.
PRF	pulse repetition frequency.
Priv	private; privately.
PROHIB	prohibited.
PRR	pulse repetition rate.
Ps	south pole; south celestial pole.
psc	per standard compass.
p stg c	per steering compass.
Pub.	publication.
PV	prime vertical.
Pyl	pylon.

Q

Q	quick flashing.
Q(3)	group quick flashing (3 flashes).
Q(6)+L.Fl.	group quick flashing (6 flashes) plus a long flash.
Q	Polaris correction.
QQ'	celestial equator.

R

r	end of own ship's true vector.
R	Rankine (temperature); refraction; own ship; red; rocky; coast radio station.
RA	right ascension.
RACON	radar transponder beacon.
rad	radian(s).
RB	relative bearing.
R Bn	radiobeacon.
RCC	Rescue Coordination Center.
RDF	radio direction finder, RDF station.
Rep.	reported.
rev.	reversed.
RF (rf)	radio frequency.
R Fix	running fix.
rk	rock, rocky.
RLG	ring laser gyro.
rm	relative DRM-SRM vector.
R Mast	radio mast.
RORO	roll-on/roll-off.
RML	relative movement line.
RMS	root mean square.
RSS	root sum square.
RTCM	Radio Technical Commission for Maritime Services.
RZn	relative azimuth.

S

s	second(s).
S	sea-air temperature difference correction; slow; south; set; speed; sand.

SALM	single anchor leg mooring.	TD	time difference (Loran C).
SAM	system area monitor.	Tel	telephone; telegraph.
SAR	search and rescue.	TG	time difference of groundwaves from master and secondary (slave) stations (Loran).
SART	search and rescue radar transponder.		
SBM	single buoy mooring.	TGS	time difference of groundwave from master and skywave from secondary (slave) station (Loran).
SD	semidiameter; sounding doubtful.	TH	true heading.
sec	secant.	TMG	track made good.
sec.	second, seconds.	TOD	time of day (clock).
semidur.	semiduration.	Tk	tank.
SENC	system electronic navigation chart.	TR	track.
SES	ship earth station.	Tr	transit; tower.
SF	Secondary Phase Factor.	Ts	time difference of skywaves from master and secondary (slave) stations (Loran).
SH	ship's head (heading).	TSG	time difference of skywave from master and groundwave from secondary (slave) station (Loran).
SHA	sidereal hour angle.	TSS	traffic separation scheme.
SHF	super high frequency.	TZn	true azimuth.
SI	International System of Units.		
SID	sudden ionospheric disturbance.		
sin	sine.		
SINS	Ships Inertial Navigation System.		
SLD	sea level datum.		
SMG	speed made good.		
SNR	signal-to-noise ratio.		
SOA	speed of advance.		
SOG	speed over ground.		
SOLAS	Safety of Life at Sea Convention.	U	upper limb correction for moon.
SP	spire; spherical.	UHF	ultra high frequency.
SPA	sudden phase anomaly.	UL	upper limb.
SPM	single point mooring.	Uncov	uncovers.
SRM	speed of relative movement.	UPS	Universal Polar Stereographic.
SS	signal station.	U.Q.	ultra quick flashing.
U.S. Sur M	U.S. Survey mile(s).	USGS	United States Geodetic Survey.
sub, subm	submerged.	USWMS	Uniform State Waterway Marking System.

T

T	air temperature correction (altitude); table; temperature; time; toward (altitude intercept); true (direction).
t	dry-bulb temperature; elapsed time; meridian angle.
t'	wet-bulb temperature.
tab.	table.
TAI	International Atomic Time.
tan	tangent.
TB	true bearing; turning bearing; air temperature atmospheric pressure correction (altitude).
TC	true course.
TCA	time of satellite closest approach.
TCPA	time to closest point of approach.
TcHHW	tropic higher high water.
TcHHWI	tropic higher high water interval.
TcHLW	tropic higher low water.
TcLHW	tropic lower high water.
TcLLW	tropic lower low water.
TcLLWI	tropic lower low water interval.

V

v	variation; vertex.
var.	excess of GHA change from adopted value for 1 hour.
vel	variation.
Ver	velocity.
VHF	vertical.
VHSD	very high frequency.
Vi	very high speed data.
VLCC	violet.
VLF	very large crude carrier.
VPF	very low frequency.
	vector product format.

V

vol	volcano; volcanic.	WT	watch time.
VPF	vector product format.		
V.Q.	very quick flashing.		X – Y – Z
V.Q.(3)	group very quick flashing.		
VRM	variable range marker.		
VTS	vessel traffic service.	X	parallactic angle.
		XMTR	transmitter.
		y.	yellow.
		yd(s).	yard(s).
		yr(s).	year(s).
		z	zenith distance.
W	west; white.	Z	azimuth angle; zenith.
WARC	World Administrative Radio Council.	ZD	zone description.
WE	watch error.	Z Diff.	azimuth angle difference.
WGS	World Geodetic System.	Zn	azimuth.
Wk	wreck.	Znpgc	azimuth per gyrocompass.
WMO	World Meteorological Organization.		
WWNWS	World Wide Navigational Warning Service.		

